



TECHNICAL DATA SHEET ROOF SEALER

Roof Sealer is a water based 100% acrylic sealer that can be used on a variety of substrates including concrete roof surfaces, unglazed terracotta roof tiles, along with metal, zincalume and Colorbond® roof surfaces.

APPLICATION & USAGE:

Tip Size	517
Touch Dry Overcoat	30 mins 2 hours
Coverage	8 - 10m ² per litre
Wash Up	Water
Thinner	Not Recommended

The above figures are based on 25°c and 50% relative humidity. Coverage rates are a guide only. As the porosity of different substrates vary, the applicator must ensure sufficient primer is applied to seal the substrate. Once suitably primed, there should be a visible shine evident on the surface.

HEALTH & SAFETY:

May cause an allergic skin reaction. Harmful to aquatic life. Keep out of reach of children. Read label before use. Avoid breathing gas, mist, vapours, or spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective clothing, gloves, eye/face protection and a suitable respirator as required. Avoid release to the environment.

FIRST AID: For advice, contact a Doctor or Poisons Information Centre (Phone Australia 13 11 26; New Zealand 0800 764 766) and have the product container or label at hand. See SDS for more information.

Ingestion: If swallowed, rinse mouth with water. Give a glass of water. If vomiting occurs, give further water. Contact a poisons information centre or doctor for advice.

Skin Contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering, or irritation occurs, seek medical advice.

Inhalation: If inhaled, remove from contaminated area into fresh air. Remove contaminated clothing. Allow patient to assume a comfortable position. Keep warm and at rest until fully recovered. If symptoms develop seek medical advice.

Eye Contact: If in eyes, hold eyelids apart and immediately flush the eye continuously with running water for 15 minutes. If irritation occurs, seek medical advice.

FIRE: If material is involved in a fire use water fog, foam, or dry agent.

STORAGE & DISPOSAL: Store in a cool, well-ventilated place away from sunlight and oxidising agents. Dispose of contents/container in accordance with local, regional, national, and international regulations.

RECOMMENDATIONS & PRECAUTIONS:

Use this product in a well-ventilated area.

Ensure that the application is in accordance with our recommendations.

Due care and consideration should be taken where water collection methods are present. We recommend allowing 14 days curing and an initial rinse (rain or tap water wash) prior to reconnecting water collection systems.

The surface preparation is the responsibility of the Builder, Renovator, Contractor, or Applicator. It is also the responsibility of the Applicator to ensure that the substrate is of an acceptable standard prior to the application of Roof Top Restore Coatings.

DISCLAIMER:

The recommendations and data provided in this document are true and accurate at the time of testing. The information is given in good faith but without any guarantee as conditions and methods of use of our product is beyond our control. We recommend that the applicator of this product conducts a small test patch in an inconspicuous area to determine the suitability of the material and its recommendations prior to use or application.